

Dane aktualne na dzień: 23-04-2024 13:51

Link do produktu: <https://www.poweraudio.pl/accuton-ceramic-bass-midrange-c220-06-221-p-6995.html>



Accuton Ceramic Bass-Midrange C220-06-221

Cena	2 799,99 zł
Czas wysyłki	Do 24 godziny
Kod EAN	Średnia cena 30 dni 2019,99
Producent	Accuton

Opis produktu





**8,5-calowy bas-średniotonowy dla 2- lub 3-drożnych kolumn podłogowych.
Średniej wielkości cewka drgająca z 38-milimetrową tytanową cewką drgającą zapewniającą wysoką rozdzielczość średnich tonów.
Wersja z impedancją 6 OHM**

MECHANICAL DATA		
SPECIFICATION	VALUE	UNIT
OVERALL DIAMETER	220	MM
CUTOUT DIAMETER/SQUARE	191	MM
MIN. FRONTPLATE THICKNESS	9	MM
OVERALL DEPTH	105	MM
MOTOR ASSEMBLY DEPTH	42	MM
MOTOR ASSEMBLY DIAMETER	120	MM
SCREWFITTING	DIN 7984 / Ø 4.50	MM
TERMINAL	+: 6.3 X 0.8 / -: 4.8 X 0.8	MM
SHIPPING WEIGHT (PAIR)	6.6	KG
SHIPPING BOX SIZE (PAIR)	250/290/250	MM

Do zastosowania w obudowie bass-reflex:

Vb: 51L, Port diameter: 70mm, Length: 265mm, Fres: 26.5Hz, F-3dB: 34Hz, Q: 0.58 (optimal)
 Vb: 83L, Port diameter: 70mm, Length: 110mm, Fres: 29Hz, F-3dB: 28Hz, Q: 0.50 (extended bass)
 Vb: 43L, Port diameter: 70mm, Length: 220mm, Fres: 31Hz, F-3dB: 35Hz, Q: 0.61 (0.7dB Ripple @ 50Hz)

Obudowa zamknięta:

Vb: 29L, -6dB @ 40Hz, -19dB @ 20Hz, F-3dB: 50Hz, Q: 0.71 (typical)
 Vb: 83L, -4.5dB @ 40Hz, -13dB @ 20Hz, F-3dB: 60Hz, Q: 0.50 (extended bass)

THIELE/SMALL PARAMETERS

SPECIFICATION		VALUE	UNIT
SENSITIVITY (2.83V / 1M)	SPL	88	DB
DC-RESISTANCE)	RE	6.3	OHM
RESONANCE FREQUENCY	FS	26.3	HZ
EQUIVALENT VOLUME OF AIR	VAS	86.2	LTR
MECHANICAL Q	QMS	7.1	
ELECTRICAL Q	QES	0.42	
TOTAL Q	QTS	0.40	
EFFECTIVE PISTON AREA	SD	224	CM2
MOVING MASS	MMS	30.4	G
SUSPENSION COMPLIANCE	CMS	1.20	MM/N
MECHANICAL RESISTANCE	RMS	0.71	KG*S



