

---

Dane aktualne na dzień: 30-09-2026 16:06

Link do produktu: <https://www.poweraudio.pl/dayton-audio-rss315ho-4-12-reference-ho-subwoofer-4-ohm-black-alu-cone-pe-295-466-p-2759.html>



## Dayton Audio RSS315HO-4 12" Reference HO Subwoofer 4 Ohm. Black alu. cone PE 295-466

|            |                           |
|------------|---------------------------|
| Cena       | <b>1 478,25 zł</b>        |
| Dostępność | <b>Dostępność - 3 dni</b> |
| Producent  | <b>Dayton Audio</b>       |

### Opis produktu

#### Dayton Audio RSS315HO-4



#### Quick Overview:

The Dayton Audio Reference Series subwoofers take the quality and performance of the much acclaimed RS line into the subwoofer realm. The black anodized cone, rubber surround, and custom basket give this driver a unique, high-end look.

---



### Product Highlights:

- Extensively vented motor eliminates compression and allows quiet excursion
  - Extra-thick black anodized aluminum cone for maximum rigidity
    - Triple shorting ring motor for ultra-low distortion
      - 4-layer coil for high power handling
    - Optimized parameters for small enclosures
  - Highest quality materials throughout for long-lasting performance






**Note: All dimensions in mm.**




**Note: All dimensions in mm.**

## Frequency Response



Note: Due to testing limitations, response below 200 Hz is not an actual representation.

## Impedance/Phase



| Parameters                  |          |
|-----------------------------|----------|
| Impedance ( $\Omega$ )      | 4        |
| Re ( $\Omega$ )             | 3.4      |
| Le (mH) @ 1 kHz             | 1.93     |
| Fs (Hz)                     | 31.6     |
| Qms                         | 4.27     |
| Qes                         | 0.45     |
| Qts                         | 0.41     |
| Mms (g)                     | 280.9    |
| Cms (mm/N)                  | 0.09     |
| Sd (cm <sup>2</sup> )       | 514.7    |
| Vd (cm <sup>3</sup> )       | 633.1    |
| BL (Tm)                     | 20.70    |
| VAS (liters)                | 33.5     |
| XMAX (mm)                   | 12.3     |
| VC Diameter (mm)            | 64       |
| SPL (dB@1W/1m)              | 85.0     |
| RMS Power Handling (w)      | 700      |
| Usable Frequency Range (Hz) | 26 - 600 |