

Link do produktu: <https://www.poweraudio.pl/scan-speak-illuminator-18wu8747t00-p-3147.html>



# Scan Speak Illuminator 18WU/8747T00

Cena	1 379,99 zł
Dostępność	Dostępność - 3 dni
Czas wysyłki	Do 24 godziny
Producent	Scan Speak

## Opis produktu

### 18WU/8747T00

The Illuminator woofers are in every aspect unusual designs with the open construction, the extremely long linear excursion and patented under-hung SD-3 (Symmetrical Drive) neodymium motor system, which due to copper caps and its construction ensures very low distortion, adding the unique patented cones, low-loss linear suspension the result is: “The Very Best Money Can Buy”!

**KEY FEATURES:**

- Under-Hung Neodymium Motor Design
- Black Anodized Alu. Cone
- Low-Loss linear suspension
- Patented Symmetrical Drive (SD-3)
- Exceptionally Long Linear Excursion
- Patented Design

T-S Parameters	
Resonance frequency [fs]	33 Hz
Mechanical Q factor [Qms]	3.31
Electrical Q factor [Qes]	0.35
Total Q factor [Qts]	0.32
Force factor [Bl]	7.5 Tm
Mechanical resistance [Rms]	1.00 kg/s
Moving mass [Mms]	16 g
Suspension compliance [Cms]	1.45 mm/N
Effective diaph. diameter [D]	140 mm
Effective piston area [Sd]	154 cm²
Equivalent volume [Vas]	48.3 l
Sensitivity (2.83V/1m)	85.5 dB
Ratio Bl/√Re	3.09 N/√W
Ratio fs/Qts	104 Hz

**Notes:**  
IEC specs. refer to IEC 60268-5 third edition.  
All Scan-Speak products are RoHS compliant.  
Data are subject to change without notice.  
Datasheet updated: February 22, 2011.

Electrical Data	
Nominal impedance [Zn]	8 Ω
Minimum impedance [Zmin]	7.7 Ω
Maximum impedance [Zo]	61.7 Ω
DC resistance [Re]	5.9 Ω
Voice coil inductance [Le]	0.41 mH

Power Handling	
100h RMS noise test (IEC 17.1)	80 W
Long-term max power (IEC 17.3)	150 W

Voice Coil and Magnet Data	
Voice coil diameter	42 mm
Voice coil height	8 mm
Voice coil layers	4
Height of gap	20 mm
Linear excursion	± 9 mm
Max mech. excursion	± 16 mm
Unit weight	1.7 kg

