Link do produktu: https://www.poweraudio.pl/scan-speak-revelator-32w4878t01-p-3180.html



Scan Speak Revelator 32W/4878T01

Cena	3 179,99 zł
Dostępność	Dostępność - 3 dni
Czas wysyłki	Do 24 godziny
Producent	Scan Speak

Opis produktu

32W/4878T01

The 32W/4878T01 is a powerful woofer designed by Scan-speak. Its large 3" voice coil and low resonance frequency is perfect to reproduce low to mid frequencies at with high efficiency. It features a brand new type of paper-sandwich cone with a special foam filling technology (patented) that gives the cone very high stiffness and relative low weight. The motor system has heavy-duty copper sleeves for optimizing eddy currents effect and minimized self-induction.



KEY FEATURES:

- Paper sandwich cone with Patented foam fillin
 Patented Symmetrical Drive motor
- Patented Symmetrical Drive motor
 Spider with balanced woven in tinsel leads

T-S Parameters	
Resonance frequency [fs]	23 Hz
Mechanical Q factor [Qms]	6.0
Electrical Q factor [Qes]	0.30
Total Q factor [Qts]	0.28
Force factor [BI]	13 Tm
Mechanical resistance [Rms]	2.7 kg/s
Moving mass [Mms]	112 g
Compliance [Cms]	0.43 mm/N
Effective diaph. diameter [D]	260 mm
Effective piston area [Sd]	531 cm ²
Equivalent volume [Vas]	170 I
Sensitivity (2.83V/1m)	92 dB
Ratio BI/√Re	7.4 N/√W
Ratio fs/Qts	82 Hz

Notes: IEC specs. refer to IEC 60268-5 third edition. All Scan-Speak products are RoHS compliant Data are subject to change without notice. Datasheet updated: April 5, 2013. Lin. excursion (±7.0 mm) with high efficiency
 3" Voice coil, Titanium former and paper reinforced
 Stiff and strong die cast aluminium chassis

Electrical Data	
Nominal impedance [Zn]	4 Ω
Minimum impedance [Zmin]	- Ω
Maximum impedance [Zo]	- Ω
DC resistance [Re]	3.1 Ω
Voice coil inductance [Le]	0.3 mH
Power Handling	
100h RMS noise test (IEC 17.1)	350 W
Long-term max power (IEC 17.3)	700 W
Voice Coil & Magnet Data	
Voice coil diameter	75 mm
Voice coil height	22 mm
Voice coil layers	2
Height of gap	8 mm
Linear excursion	± 7 mm
Max mech. excursion	± 28 mm

